

AVL DITEST MDS MOBILE – MODULAR DIAGNOSTIC SYSTEM

TRANSPORTEINHEIT



Miscellaneous

Dimensions	535 x 320 x 240 (W x H x D)
Weight	Ca. 15 kg

Power Supply

Voltage Supply	230 VAC
Power Consumption	Ca. 150 W

AVL DITEST MDS MOBILE – MODULAR DIAGNOSTIC SYSTEM

AVL DITEST GAS 2301



Miscellaneous	
Warm-up Time	Approx. 2 min
Operating Temperature	5 ... 40 °C
Storage Temperature	0 ... 50°C
Humidity	10 ... 90 % non condensing
Dimensions	344 x 252 x 85 (W x H x D)
Weight	2.2 kg
Interfaces	USB, Bluetooth Class 1, RS 232 (AK Protokoll)
Certification	2014/32/EU (MID); OIML R99 Class 0

Versorgung	
Voltage Supply	Via AVL DiTEST CDS Basic Unit: 11..25 V DC
Power Consumption	Approx. 20 VA

Measurand	Measuring	Resolution	Accuracy
CO	0 ... 15 % vol	0,01 % vol.	< 0,6 % vol: ± 0.03 % vol ≥ 0,6 % vol: ± 5 % o. M.
CO2	0 ... 20 % vol.	0,01 % vol.	< 10 % vol: ± 0.5 % vol ≥ 10 % vol: ± 5 % o. M.
HC	0 ... 30.000 ppm vol.	≤ 2.000: 1 ppm vol.	< 200 ppm vol: ± 10 ppm vol ≥ 200 ppm vol: ± 5 % o. M. ≥ 10000 ppm vol: ± 10 % o. M.
O2	0 ... 25 % vol.	0,01 % vol.	< 2 % vol: ± 0.1 % vol ≥ 2 % vol: ± 5 % o. M.
NO (optional)	0 ... 5.000 ppm vol.	1 ppm vol.	< 500 ppm vol: ± 50 ppm vol ≥ 500 ppm vol: ± 10 % o. M.
Lambda	0 ... 9.999	0,001	Calculated from CO, CO2, HC, O2

AVL DITEST MDS MOBILE – MODULAR DIAGNOSTIC SYSTEM

AVL DISMOKE 480 BT



Technical Data	
Measuring Principle	Extinction Measurement
Operating Temperature	+5 ... +40 °C
Storage Temperature	-20 ... +60 °C
Humidity	max. < 90 %, non condensing
Nominal Voltage	230 VAC
Voltage Range	85 - 264 VAC
Frequency	47 ... 63 Hz
Power Consumption	approx. 78 VA (incl. heating)
Dimensions	395 x 285 x 136 (W x H x D)
Weight	3,5 kg
Interfaces	RS232; Bluetooth Class1

Opacity Chamber	
Chamber Heating	100 °C
Measurement Length	215 mm ± 2 mm
Max. Emission Temperature	200 °C
Opacity	- Messbereich: 0 ... 99,9% - Auflösung: 0,1 %
Absorption (k-Value)	- Messbereich: 0 ... 9,99% - Auflösung: 0,01/m

AVL DITEST MDS MOBILE – MODULAR DIAGNOSTIC SYSTEM

AVL DITEST AUX 2000



Measurement Parameters (optional) RPM and oil temperature	Measuring Range
Engine	4-Stroke-Diesel- and Gasoline Engines
RPM Diesel Engines	400 6.000 min-1
Drehzahl Gasoline Engines	400 ... 8.000 min-1
RPM Ranges	Idle Speed 400 ... 1.200 min-1 High RPM I 1.700 ... 6.000 min-1
Signal Input	AVL DITEST magnetic sensor
Oil Temperature	-10.... 145 °C
Signal Input	AVL DITEST oil temperature Probe

Climatic conditions	
Operating Temperature	+4 ... +40 °C
Storage Temperature	-20 ... +50 °C
Humidity	10 ... 90% non condensing

Schnittstellen	
AVL DiSPEED 492 connector	- Connection for external DISPEED 490/492
AVL Dual sensor connector	- Connection for magnetic sensor (Art.Nr.:
Oil temperature probe	- Connection for oil temperature probe (Art.Nr.):)
connection	USB, Bluetooth Class 1

Dimesion/Weight	
Dimensions	235 x 162 x 60 (W x H x D)
Storage Temperature	0,8 kg

AVL DITEST MDS MOBILE – MODULAR DIAGNOSTIC SYSTEM

AVL DITEST VCI 1000 ODER OBD 1000



Power Supply	
Nominal Voltage	+12 V (DC)
Voltage Range	+6 ... +36 V (DC)/0,4 A

Power Supply	
Nominal Voltage	+12 V (DC)
Voltage Range	+8 ... +34 V (DC), max. 3W

Temperature	
Operation temperature	0°C ... +40°C
Transport temperature	-20°C ... +60°C
Humidity	10% ... 90% (not condensating)

Temperature	
Operation temperature	0°C ... +40°C
Transport temperature	-20°C ... +60°C
Humidity	10% ... 90% (not condensating)

Housing	
Weight	120g
Dimensions (T x B x H)	121,5 x 50 x 25mm

Housing	
Weight	95g
Dimensions (T x B x H)	118 x 48 x 25mm

Interfaces	
Personal Computer (PC):	Mini USB 2.0 Type B-Buchse (USB1.1)
Vehicle:	OBD-plug (16-pin)
supported vehicle-Protocols:	(AU)/(E)OBD/OBDII conform protocols All vehicle manufacturers specific protocols (e.g. K-line, CAN, PWM/VPW, SCP, GMLAN, UDS, KWP2000, TP2.0, ...)

Schnittstellen	
Personal Computer (PC):	Mini USB 2.0 Type B-plug (USB1.1)
Vehicle:	OBD-plug (16-pin)
supported vehicle-Protocols:	(AU)/(E)OBD/OBDII/WWH/OBD conform protocols